


CLIPPO S DUO DIM TO WARM


SPECIFICATIONS

MOUNTING		CEILING / WALL
POWER	[W]	2x9,5
LAMP		built-in LED
LUMINOUS FLUX*	[lm]	2x45-915
LIGHT COLOUR	[K]	1910-3000
CRI		>90
BEAM ANGLE	[°]	34 (default)
AVERAGE LIFETIME	[h]	L80/B50.000
LUMINOUS EFFICACY	[lm/W]	96
POWER SUPPLY	[V] [A]	220-240V AC 50/60 Hz
LED-DRIVER		INCLUDED
DIMMING		PHASE DIM
THROUGH-WIRING		YES
MATERIAL		ALUMINUM
INGRESS PROTECTION		IP20
PROTECTION CLASS		I
NET WEIGHT	[kg]	0,92
GROSS WEIGHT	[kg]	0,98
COLOUR (HOUSING)		WHITE ~RAL9003
COLOUR (HOUSING)		BLACK ~RAL9005



LIGHT DISTRIBUTION

34°



*Luminous flux values are nominal LED data at a operating temperature of 25° C

OPTIONS / OPTIONAL ACCESSORIES

REFLECTOR	[°]	24 / 48
HONEY COMB LOUVER		BLACK
ANTI GLARE RING		GOLD
DIMMING		DALI (ON REQUEST)



Colours




white/white

white/gold


black/black

black/gold

MOUNTING DIMENSIONS



FIXTURE DIMENSIONS



CRI > 90

dim to warm



IP20

DLS LIGHTING


www.dslighting.com

***DLS**
LIGHTING

CLIPPO S DUO 2700K


SPECIFICATIONS

MOUNTING		CEILING / WALL
POWER	[W]	2x9,5
LAMP		built-in LED
LUMINOUS FLUX*	[lm]	2x1100
LIGHT COLOUR	[K]	2700
CRI		>90
BEAM ANGLE	[°]	34 (default)
AVERAGE LIFETIME	[h]	L80/B50.000
LUMINOUS EFFICACY	[lm/W]	118
POWER SUPPLY	[V] [A]	220-240V AC 50/60 Hz
LED-DRIVER		INCLUDED
DIMMING		PHASE DIM
THROUGH-WIRING		YES
MATERIAL		ALUMINUM
INGRESS PROTECTION		IP20
PROTECTION CLASS		I
NET WEIGHT	[kg]	0,92
GROSS WEIGHT	[kg]	0,98
COLOUR (HOUSING)		WHITE ~RAL9003
COLOUR (HOUSING)		BLACK ~RAL9005



LIGHT DISTRIBUTION

34°



*Luminous flux values are nominal LED data at a operating temperature of 25° C

OPTIONS / OPTIONAL ACCESSORIES

REFLECTOR	[°]	24 / 48
HONEY COMB LOUVER		BLACK
ANTI GLARE RING		GOLD
DIMMING		DALI (ON REQUEST)



Colours




white/white

white/gold


black/black

black/gold

MOUNTING DIMENSIONS



FIXTURE DIMENSIONS



DLS LIGHTING

www.dslighting.com

***DLS**
LIGHTING