

ZOOM

SPECIFICATIONS

MOUNTING		WALL / CEILING RECESSED
POWER	[W]	2
LAMP		built-in LED
LUMINOUS FLUX*	[lm]	190
LIGHT COLOUR	[K]	3000
CRI		>90
BEAM ANGLE	[°]	15 - 60
AVERAGE LIFETIME	[h]	L80/B50.000
LUMINOUS EFFICACY	[lm/W]	95

POWER SUPPLY	[V] [A]	500mA CC
LED-DRIVER		NOT INCLUDED
DIMMING		SEE DRIVER
THROUGH-WIRING		SEE DRIVER

MATERIAL		BRASS
INGRESS PROTECTION		IP20
PROTECTION CLASS		III
NET WEIGHT	[kg]	0,06
GROSS WEIGHT	[kg]	0,06
COLOUR (HOUSING)		WHITE ~RAL9003
COLOUR (HOUSING)		BLACK ~RAL9005
COLOUR (HOUSING)		CHROME
COLOUR (HOUSING)		PLATINUM

CUT-OUT	[mm]	Ø41
RECESSED DEPTH (H)	[mm]	27

*Luminous flux values are nominal LED data at a operating temperature of 25° C




LIGHT DISTRIBUTION

n/a

OPTIONS / OPTIONAL ACCESSORIES

MOUNTING BOX for brickwall
2700K and 4000K LED on request



Colours



white


black

chrome




platinum

CUT OUT DIMENSIONS



FIXTURE DIMENSIONS



DLS LIGHTING

www.dslighting.com

***DLS**
LIGHTING