

PHANTOM

SPECIFICATIONS

MOUNTING		WALL / CEILING RECESSED
POWER	[W]	20W G4 or 2W LED
LAMP		LED-built-in or HALOGEN
LUMINOUS FLUX*	[lm]	190 (LED)
LIGHT COLOUR	[K]	3000
CRI		>90
BEAM ANGLE	[°]	-
AVERAGE LIFETIME	[h]	L80/B50.000
LUMINOUS EFFICACY	[lm/W]	95
POWER SUPPLY	[V] [A]	500mA cc (LED) or 12V (G4)
LED-DRIVER		NOT INCLUDED
DIMMING		SEE DRIVER
THROUGH-WIRING		SEE DRIVER
MATERIAL		ALUMINUM
INGRESS PROTECTION		IP20
PROTECTION CLASS		III
NET WEIGHT	[kg]	0,24
GROSS WEIGHT	[kg]	0,25
COLOUR (HOUSING)		ALU
CUT-OUT	[mm]	ø50
RECESSED DEPTH (H)	[mm]	50



LIGHT DISTRIBUTION

n/a

*Luminous flux values are nominal LED data at a operating temperature of 25° C

OPTIONS / OPTIONAL ACCESSORIES

LED COLOUR OPTIONS:


- BLUE ■
- RED ■
- GREEN ■
- AMBER ■

Colours




alu

CUT OUT DIMENSIONS



FIXTURE DIMENSIONS



DLS LIGHTING

www.dslighting.com

***DLS**
LIGHTING