

CITY XS

SPECIFICATIONS

MOUNTING		CEILING RECESSED
POWER	[W]	3x3,4
LAMP		built-in LED
LUMINOUS FLUX*	[lm]	610
LIGHT COLOUR	[K]	3000
CRI		>90
BEAM ANGLE	[°]	36
AVERAGE LIFETIME	[h]	L80/B50.000
LUMINOUS EFFICACY	[lm/W]	64
POWER SUPPLY	[V] [A]	1050mA CC
LED-DRIVER		NOT INCLUDED
DIMMING		SEE DRIVER
THROUGH-WIRING		SEE DRIVER
MATERIAL		ALUMINUM
INGRESS PROTECTION		IP20
PROTECTION CLASS		III
NET WEIGHT	[kg]	0,19
GROSS WEIGHT	[kg]	0,20
COLOUR (HOUSING)		WHITE ~RAL9003
COLOUR (HOUSING)		GOLD
CUT-OUT	[mm]	Ø77
RECESSED DEPTH (H)	[mm]	105



LIGHT DISTRIBUTION


36°

n/a

*Luminous flux values are nominal LED data at a operating temperature of 25° C

OPTIONS / OPTIONAL ACCESSORIES

Colours




white



gold

CUT OUT DIMENSIONS



FIXTURE DIMENSIONS



DLS LIGHTING

www.dslighting.com

***DLS**
LIGHTING