

ZOOM AB FLEX SWITCH

SPECIFICATIONS

MOUNTING		WALL
POWER	[W]	2
LAMP		built-in LED
LUMINOUS FLUX*	[lm]	190
LIGHT COLOUR	[K]	3000
CRI		>90
BEAM ANGLE	[°]	15 - 60
AVERAGE LIFETIME	[h]	L80/B50.000
LUMINOUS EFFICACY	[lm/W]	95
POWER SUPPLY	[V] [A]	500mA cc
LED-DRIVER		NOT INCLUDED
DIMMING		SEE DRIVER
THROUGH-WIRING		SEE DRIVER

MATERIAL		BRASS
INGRESS PROTECTION		IP20
PROTECTION CLASS		III
NET WEIGHT	[kg]	0,27
GROSS WEIGHT	[kg]	0,28

COLOUR (HOUSING)	BLACK ~RAL9005
COLOUR (HOUSING)	CHROME
COLOUR (HOUSING)	PLATINUM

CUT-OUT	[mm]	Ø14 (SWITCH DIAMETER)
RECESSED DEPTH (H)	[mm]	20 (SWITCH DEPTH)

*Luminous flux values are nominal LED data at a operating temperature of 25° C



LIGHT DISTRIBUTION

n/a

OPTIONS / OPTIONAL ACCESSORIES

2700K and 4000K LED on request

Colours




black


chrome

platinum

MOUNTING DIMENSIONS



FIXTURE DIMENSIONS



DLS LIGHTING

www.dlsighting.com

***DLS**
LIGHTING