

MK Q

SPECIFICATIONS


MOUNTING		CEILING RECESSED
POWER	[W]	10
LAMP		built-in LED
LUMINOUS FLUX*	[lm]	1060
LIGHT COLOUR	[K]	3000
CRI		>90
BEAM ANGLE	[°]	40
AVERAGE LIFETIME	[h]	L80/B50.000
LUMINOUS EFFICACY	[lm/W]	106
POWER SUPPLY	[V] [A]	220-240V AC 50/60 Hz
LED-DRIVER		INCLUDED
DIMMING		NO
THROUGH-WIRING		NO
MATERIAL		ALUMINUM
INGRESS PROTECTION		IP44
PROTECTION CLASS		III
NET WEIGHT	[kg]	0,29
GROSS WEIGHT	[kg]	0,30
COLOUR (HOUSING)		WHITE ~RAL9003
CUT-OUT	[mm]	75x75
RECESSED DEPTH (H)	[mm]	120

*Luminous flux values are nominal LED data at a operating temperature of 25° C




LIGHT DISTRIBUTION

40°




OPTIONS / OPTIONAL ACCESSORIES

Colours




white

CUT OUT DIMENSIONS



FIXTURE DIMENSIONS



DLS LIGHTING

www.dslighting.com

***DLS**
LIGHTING