

SMILE

SPECIFICATIONS

MOUNTING		WALL RECESSED
POWER	[W]	2
LAMP		built-in LED
LUMINOUS FLUX*	[lm]	190
LIGHT COLOUR	[K]	3000
CRI		>90
BEAM ANGLE	[°]	-
AVERAGE LIFETIME	[h]	L80/B50.000
LUMINOUS EFFICACY	[lm/W]	95

POWER SUPPLY	[V] [A]	500mA cc
LED-DRIVER		NOT INCLUDED
DIMMING		SEE DRIVER
THROUGH-WIRING		SEE DRIVER

MATERIAL		ALUMINUM
INGRESS PROTECTION		IP20
PROTECTION CLASS		III
NET WEIGHT	[kg]	0,05
GROSS WEIGHT	[kg]	0,05

COLOUR (HOUSING)		WHITE ~RAL9003
COLOUR (HOUSING)		BLACK
COLOUR (HOUSING)		CHROME
COLOUR (HOUSING)		PLATINUM

CUT-OUT (FIXTURE)	[mm]	ø36
RECESSED DEPTH (H)	[mm]	25

*Luminous flux values are nominal LED data at a operating temperature of 25° C





LIGHT DISTRIBUTION


n/a

OPTIONS / OPTIONAL ACCESSORIES

MOUNTING BOX
CONCRETE MOUNTING SLEEVE
MOUNTING RING FOR JUNCTION BOXES



Colours



white



black




chrome




platinum

CUT OUT DIMENSIONS



FIXTURE DIMENSIONS



DLS LIGHTING

www.dslighting.com

***DLS**
LIGHTING