

# CLIPPO OPTIC


## SPECIFICATIONS

|                    |         |                      |
|--------------------|---------|----------------------|
| MOUNTING           |         | CEILING / WALL       |
| POWER              | [W]     | 10,5                 |
| LAMP               |         | built-in LED         |
| LUMINOUS FLUX*     | [lm]    | 35-1240              |
| LIGHT COLOUR       | [K]     | 1800-3000            |
| CRI                |         | >90                  |
| BEAM ANGLE         | [°]     | 35 (default)         |
| AVERAGE LIFETIME   | [h]     | L80/B50.000          |
| LUMINOUS EFFICACY  | [lm/W]  | 118                  |
| POWER SUPPLY       | [V] [A] | 220-240V AC 50/60 Hz |
| LED-DRIVER         |         | INCLUDED             |
| DIMMING            |         | PHASE DIM            |
| THROUGH-WIRING     |         | YES                  |
| MATERIAL           |         | ALUMINUM             |
| INGRESS PROTECTION |         | IP20                 |
| PROTECTION CLASS   |         | I                    |
| NET WEIGHT         | [kg]    | 0,83                 |
| GROSS WEIGHT       | [kg]    | 0,86                 |
| COLOUR (HOUSING)   |         | WHITE ~RAL9003       |
| COLOUR (HOUSING)   |         | BLACK ~RAL9005       |



## LIGHT DISTRIBUTION

35°



\*Luminous flux values are nominal LED data at a operating temperature of 25° C

## OPTIONS / OPTIONAL ACCESSORIES

|             |     |         |
|-------------|-----|---------|
| REFLECTOR   | [°] | 24 / 50 |
| ACCENT RING |     | GOLD    |



white/white



white/gold




black/black




black/gold



## MOUNTING DIMENSIONS



## FIXTURE DIMENSIONS



DLS LIGHTING

www.dlslighting.com

**\*DLS**  
LIGHTING