

PIXEL

SPECIFICATIONS

MOUNTING		WALL RECESSED
POWER	[W]	1
LAMP		built-in LED
LUMINOUS FLUX*	[lm]	92
LIGHT COLOUR	[K]	3000
CRI		>90
BEAM ANGLE	[°]	-
AVERAGE LIFETIME	[h]	L80/B50.000
LUMINOUS EFFICACY	[lm/W]	92

POWER SUPPLY	[V] [A]	350mA cc
LED-DRIVER		NOT INCLUDED
DIMMING		SEE DRIVER
THROUGH-WIRING		SEE DRIVER

MATERIAL		ALUMINUM, ACRYLIC GLASS
INGRESS PROTECTION		IP44
PROTECTION CLASS		III
NET WEIGHT	[kg]	0,19
GROSS WEIGHT	[kg]	0,20

COLOUR (HOUSING)		WHITE ~RAL9016
COLOUR (HOUSING)		ALU

CUT-OUT (FIXTURE)	[mm]	ø41
RECESSED DEPTH (H)	[mm]	45





LIGHT DISTRIBUTION

n/a


*Luminous flux values are nominal LED data at a operating temperature of 25° C

OPTIONS / OPTIONAL ACCESSORIES


MOUNTING BOX
CONCRETE MOUNTING SLEEVE





Colours



CUT OUT DIMENSIONS



FIXTURE DIMENSIONS



DLS LIGHTING

www.dslighting.com

***DLS**
LIGHTING